

S C M 4 0 : 3 - w a y p a s s i v e



Available in cherry and black ash veneer. Limited other finishes by special order.



Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email info@atc.gb.net Website www.atcloudspeakers.co.uk

Features

- New ATC designed and built 25mm soft dome HF unit with precision alloy wave guide.
- ATC 164mm short coil bass driver.
- Massive optimised motor assembly.
- ATC soft dome mid-range driver.
- Flat impedance curve allowing easy load for amplifiers.
- 6 year warranty.

Specifications

Drivers : HF 25mm Neodymium, Mid 75mm ATC Soft Dome, LF 164mm

Matched Response : $\pm 0.5\text{dB}$

Frequency Response (-6dB) : 48Hz-22kHz

Dispersion : $\pm 80^\circ$ Coherent Horizontal, $\pm 10^\circ$ Coherent Vertical

Sensitivity : 85dB @ 1W @ 1metre

Max SPL : 112dB

Recommended Power Amplifier : 75 to 300 Watts

Nominal Impedance : 8 Ohm

Crossover Frequencies : 380Hz & 3.5kHz

Connectors : Binding Posts/4mm Plugs, tri-wire

Cabinet Dimensions (HxWxD) : 980x265x300mm

Weight : 31kg

ATC reserves the right to vary products and specifications without prior notice.