

SCM11 : 2 - w a y p a s s i v e



Available in cherry and black ash veneer. Limited other finishes by special order.



Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email info@atc.gb.net Website www.atcloudspeakers.co.uk

Features

- New ATC designed and built 25mm soft dome HF unit with precision alloy wave guide.
- Precision undercut bass pole.
- "CLD" driver technology with 45mm integral soft dome.
- In-house, hand-wound precision flat wire coil.
- Massive optimised motor assembly.
- Flat impedance curve allowing easy load for amplifiers.
- 6 year warranty.

Specifications

Drivers : HF 25mm Neodymium, Mid/LF 150mm

Matched Response : +/- 0.5dB

Frequency Response (-6dB) : 56Hz-22kHz

Dispersion : ±80° Coherent Horizontal, ±10° Coherent Vertical

Sensitivity : 85dB @ 1W @ 1metre

Max SPL : 108dB

Recommended Power Amplifier : 75 to 300 Watts

Nominal Impedance : 8 Ohm

Crossover Frequency : 2.2kHz

Connectors : Binding Posts/4mm Plugs, bi-wire

Cabinet Dimensions (HxWxD) : 381x232x236mm

Weight : 10.9kg

ATC reserves the right to vary products and specifications without prior notice.