

# SCM19 : 2 - w a y p a s s i v e



Available in cherry and black ash veneer. Limited other finishes by special order.



## Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email [info@atc.gb.net](mailto:info@atc.gb.net) Website [www.atcloudspeakers.co.uk](http://www.atcloudspeakers.co.uk)

## Features

- New ATC designed and built 25mm soft dome HF unit with precision alloy wave guide.
- "SL" spec bass driver with 75mm integral soft dome.
- 9kg optimised short-coil/long gap motor assembly.
- In-house, hand-wound precision flat wire coil.
- Flat impedance curve allowing easy load for amplifiers.
- 6 year warranty.

## Specifications

**Drivers :** HF 25mm Neodymium, Mid/LF 150mm

**Matched Response :** +/- 0.5dB

**Frequency Response (-6dB) :** 54Hz-22kHz

**Dispersion :** ±80° Coherent Horizontal, ±10° Coherent Vertical

**Sensitivity :** 85dB @ 1W @ 1metre

**Max SPL :** 108dB

**Recommended Power Amplifier :** 75 to 300 Watts

**Nominal Impedance :** 8 Ohm

**Crossover Frequency :** 2.5kHz

**Connectors :** Binding Posts/4mm Plugs, bi-wire

**Cabinet Dimensions (HxWxD) :** 438x265x300mm

**Weight :** 17.8kg

ATC reserves the right to vary products and specifications without prior notice.